

## PCB Insp. Conveyor / LP Insp. Förderband

- PCB in ergonomic working position 15°  
LP in ergonomischer Arbeitsposition 15°
- Tilt unit 0°>15° and 15°>0°  
Schwenkstationen 0°>15° und 15°>0°
- Code-Reader fixing option (top / bottom)  
Code-Leser Befestigungsoption (oben/unten)



PCB Dimension [mm] / LP-Abmaße		Option
Length	100 - 447	on request
Width	50 - 410	on request
Thickness	0,8 - 3,0	
height top	50	
	50	
PCB -Edge	3	
Transport height	950 +/-45	

Machine Dimension [mm] / Masch.-Abmaße		Option
Length (front)	2210	
Width (depth)	1030	
Height	1810	
Weight	260 kg	

Materials / Material		Option
Main Structure	Sheet metal	
Color	RAL 7035	
Transp. Sheet	ESD - Polycarbonate	

Belt conveyor / Förderband		Option
DC-Motor	Speed-regulator seperate in/out	
Belt	flat, antistatic	

PCB Capacity / LP Kapazität		Option
Qty. Conv.	3	x (on req.)

Operator panel / Bedienung		Option
HMI panel	Push button Light-Switch	Display

Supply and Connections / Anschlüsse		Option
Voltage	230V 1L N PE 50Hz	
Power	90 W	
Interface	SMEMA	add. / others
Air pressure	0,5 MPa	

Width adjustment / Breitenverstellung		Option
Belt	manual	automatic

Tilt unit / Schwenkeinheiten		Option
0° > 15° / 15° > 0°	Pneumatic	

PLC / SPS		Option
System	Siemens S7-xxx	Line PC Network

Miscellaneous / Sonstiges		Option
Buzzer / Ton	Yes / Ja	
Stopper	No / Nein	Pneumatic
CodeReader	No / Nein	Yes / Ja

### Additional Options / zusätzliche Optionen:

- Transport flow direction from right to left
- Additional Board sensor
- Ultrasonic Board sensor
- Signal light tower 1 lamp
- Signal light tower 2 lamps

- Machine extension - add. belt conveyor
- Automatic width adjustment for extension
- Additional Safety / Interlock switch
- Stopper
- Safety panel and safety switch rail

## Functional principle, layout dimensions Funktionsprinzip, Grundriss Abmaße

- PCB transport via belt conveyor  
LP Transport mit Förderbändern

